



DISHWASHING

DISHWASHER, FI-160 L

1210309100

Dimensions and Weights

Length	mm	1.430,00
Depth	mm	780,00
Height	mm	1.580,00
Net Weight	Kg	211,00
Gross Weight	Kg	305,00
Volume packed	m3	2,79

Electricity

Electric Power	KW	37,32
Voltage 230V - I+N		
Voltage 230V - III	3x25+T - 100 A	
Voltage 400V - III+N	4x16+T - 63 A	

Gas

No

DISHWASHER, FI-160 L

Made of stainless steel AISI-304 (18/10).
 Wash capacity: 90 baskets/h.
 Splash-guard module at entry.
 Dividing curtains highly resistant to chemical agents and heat.
 Wash tank for 45 litres. Tray-filters removable for cleaning.
 Two wash-pumps, 600 W each. Tank heated by means of shielded elements, 9 kW.
 Thermostatically adjusted. (wash temperature: 60 °C).
 Built-in rinse water boiler (27 kW). Safety thermostat.
 Analogic thermometers for wash and rinse water temperature.
 Water consumption: 450 l/h.
 Magnetic switches for wash, rinse and door opening.
 Energy economiser system.
 Motor-reducer: 120 W.
 Baskets equipment: 2 x CT-10, 2 x CP-16/18, 1 x CV-16/105 and 10 cutlery containers.
 Power: 37.32 kW.
 Dimensions: 1430 x 780 x 1580 mm.

Water

Consumption (lit/h)	450,00
Pressure (Kg/cm2)	2 - 4

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	70	160	320	
DESC.HOT WATER	380	630	240	3/4"
DRAIN	810	440	130	38



DISHWASHING

DISHWASHER, FI-160 R

1210309101

Dimensions and Weights

Length	mm	1.430,00
Depth	mm	780,00
Height	mm	1.580,00
Net Weight	Kg	211,00
Gross Weight	Kg	305,00
Volume packed	m3	2,79

Electricity

Electric Power	KW	37,32
Voltage 230V - I+N		
Voltage 230V - III	3x25+T - 100 A	
Voltage 400V - III+N	4x16+T - 63 A	

Gas

No

DISHWASHER, FI-160 R

Made of stainless steel AISI-304 (18/10).

Wash capacity: 90 baskets/h.

Splash-guard module at entry.

Dividing curtains highly resistant to chemical agents and heat.

Wash tank for 45 litres. Tray-filters removable for cleaning.

Two wash-pumps, 600 W each. Tank heated by means of shielded elements, 9 kW.

Thermostatically adjusted. (wash temperature: 60 °C).

Built-in rinse water boiler (27 kW). Safety thermostat.

Analogic thermometers for wash and rinse water temperature.

Water consumption: 450 l/h.

Magnetic switches for wash, rinse and door opening.

Energy economiser system.

Motor-reducer: 120 W.

Baskets equipment: 2 x CT-10, 2 x CP-16/18, 1 x CV-16/105 and 10 cutlery containers.

Power: 37.32 kW.

Dimensions: 1430 x 780 x 1580 mm.

Water

Consumption (lit/h)	450,00
Pressure (Kg/cm2)	2 - 4

Installation

	<u>X</u>	<u>Y</u>	<u>Z</u>	<u>Diameters</u>
ELECTRICITY	70	160	320	
DESC.HOT WATER	380	630	240	3/4"
DRAIN	810	440	130	38