

## RANGE COMPOSITION

Zanussi Professional have designed and produced a complete range of refrigerated tables, that combines the dual function of worktop and refrigerated table. This versatility allows notable savings in space whilst offering functional and modular solutions to kitchen requirements.

The main benefit of this innovative new range is total flexibility: you have the possibility to compose your table to your exact personal requirements. You can order each individual unit and combine them together: structure, top, door, drawer and refrigeration unit.

We offer a basic range of 38 models but the choice is infinite.

The range presented here consists of 3 models with a temperature from -13° to -22°C. Models are available with 2 doors: 1 basic model; 1 with rear upstand; and 1 with remote refrigeration unit.



113177

## PT 3 SERIES

### FREEZER TABLES 1300 ZANUSSI PROFESSIONAL

## FUNCTIONAL AND CONSTRUCTION FEATURES

- ◆ Constructed entirely in AISI 304 stainless steel with satin finish and polished interior guaranteeing maximum reliability. 2" height-adjustable AISI 304 stainless steel feet (-15 to +80 mm). Completely removable grid support structure in AISI 304 stainless steel.

- ◆ The worktop has a height of 50 mm and is slotted into place for easy removal.

- ◆ High-density expanded polyurethane foam, 60 mm in thickness, with cyclopentane injection, guarantees exceptional, long-term insulation and notable energy savings.

- ◆ The design of the refrigeration unit allows maximum usage of the available space in the compartment. It is also mounted on a pull-out system to facilitate maintenance and cleaning (Models TRF132A and TRFA132A).

- ◆ The new central position of the refrigeration unit allows perfect air circulation in the different compartments and temperature uniformity (Models TRF132A and TRFA132A).

- ◆ These appliances are suitable for use in tropical climates (+43°C) ensuring high performance even in extreme ambient conditions.

CHARACTERISTICS	MODELS		
	TRF132A 113177	TRFA132A 113178	TRRF132A 113179
Operating temperature - min/max °C	-22/-15	-22/-15	-22/-15
Operating mode	Ventilated	Ventilated	Ventilated
Gross capacity (D.I.N. 8952) - l.	290	291	291
External dimensions - mm			
width	1274	1274	1274
depth/with open doors	700, 1110	700, 1110	700, 1110
height	850	950	850
Internal dimensions - mm			
depth	580	580	580
height	530	530	530
N° and type of door	2	2	2
Door hinges	1 Left+1 Right	1 Left+1 Right	1 Left+1 Right
N° and type of grids (included)	2, GN 1/1	2, GN 1/1	2, GN 1/1
Compressor power - HP	3/4	3/4	
N° defrost in 24 hrs.	4/16'	4/16'	4/16'
Refrigerant type	R404a	R404a	R404a
Refrigerant quantity - g.	280	280	
Refrigeration power - W	925	925	
Power - kW			
installed-electric	0.75	0.75	0.078
Noise level - dBA	58	58	
Net weight - kg.	129	130	115
Power supply - V, phases, Hz	230 V, 1N, 50	230 V, 1N, 50	230 V, 1N, 50
<b>INCLUDED ACCESSORIES</b>			
1/1 GN GREY "RILSAN" GRID	2	2	2

- ◆ The base, with water drain, is pressed and features rounded internal corners to guarantee perfect cleaning.
- ◆ Completely automatic defrosting and automatic evaporation of defrost water obtained by hot gas.
- ◆ The refrigerated tables feature: reversible, self-closing doors; recessed ergonomical handles.


- ◆ Model TRRF132A is designed for use with remote refrigeration units which means that the removal of a source of heat from the working environment solves problems of high temperatures or inadequately ventilated rooms. The remote refrigeration units are supplied with a control box that includes: a thermostatic valve, evaporator and a control panel. It is possible to have each refrigerated table connected to a specific remote refrigeration unit or to connect several appliances to a central refrigeration plant.

- ◆ The model with remote refrigeration unit is supplied as standard with an ambient drawer, 100 mm in height, above the refrigeration unit.
- ◆ CFC and HCFC free.
- ◆ All models comply with the standards required by the main international approval bodies and are H marked.

ACCESSORIES	MODELS		
	TRF132A 113177	TRFA132A 113178	TRRF132A 113179
1/1 GN GREY "RILSAN" GRID	881435	881435	881435
2 WHEELS FOR REFRIGERATORS/REFRIG.TABLES	880539	880539	880539
HACCP ADV.CONN.10 UNITS-DIG.REF.(ID9XX)	880119	880119	880119
HACCP ADV.CONN.80 UNITS-DIG.REF.(ID9XX)	880132	880132	880132
HACCP ADV.CONN.PER UNIT-DIG.REF.(ID9XX)	880133	880133	880133
KIT HACCP EKIS	922166	922166	922166
LOCK FOR REFRIGERATED COUNTERS	881499	881499	881499
PLASTIC CONTAINER GN 1/1 H=100 MM	811451	811451	811451
PLASTIC CONTAINER GN 1/1 H=150 MM	881040	881040	881040
PLASTIC CONTAINER GN 1/1 H=65 MM	881038	881038	881038
PRINTER FOR HACCP BASIC VERSION REFRIG.	881457	881457	881457
REMOTE UNIT -24-15°C FOR 550/650 LT			881465




[www.zanussiprofessional.com](http://www.zanussiprofessional.com)



	TRF132A 113177	TRRF132A 113179
D - Water drain	16mm	16mm
EI - Electrical connection	230 V, 1N, 50	230 V, 1N, 50



[www.zanussiprofessional.com](http://www.zanussiprofessional.com)



	TRFA132A 113178
D - Water drain	16mm
EI - Electrical connection	230 V, 1N, 50



www.zanussiprofessional.com