



900 Series

Boiling pans 900

GAS BOILING PAN, MG9-10 BM

DIMENSIONS

		Article	Packed
Length	mm	850,00	900,00
Depth	mm	900,00	1.050,00
Height	mm	850,00	1.190,00
Weigth	Kg	125,00	156,00
Volumen	m3	0,65	1,12

ELECTRICITY

Electric power	KW	0,05
230V -1+N	2x1,5+T - 2 A	
230V - III		
400V - III+N		

WATER

Not used

GAS

Power	KW	17,80
	Kcal/h	15.308,00
LPG	Consumption (kg/h)	1,40
	Pressure (g/cm2)	37,00
Natural Gas	Consumption (m3/h)	1,79
	Pressure (g/cm2)	18,00

STEAM

Not used

AIR

Not used

GAS BOILING PAN, MG9-10 BM

Made of stainless steel.

Bottom of the well in stainless steel AISI-316-L.

Capacity: 100 litres. Double jacket pan (bain-marie system).

Counterweighted folding lid.

Stainless steel burner, with safety valve and thermocouple.

Piezoelectric ignition.

Safety device for the bain-marie extinguishes the burner in the event of low water level.

Cold and hot water filling tap.

Drainage tap.

Filling tap and control tap for the level of the double jacket pan (bain-marie). Level indicator.

Over-pressure safety valve and manometer.

Power: 15300 kcal/h. (17.8 kW).

Electrical connection: 230 V -1+N+E.

Dimensions: 850 x 900 x 850 mm.

Certificate EQNET- CE

99AP54

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	645	860	500		Válvula electromagnética
DRAIN	300	860	110		
SOFT HOT WATER	120	860	110	1/2"	Prever llave de corte en la toma
COLD WATER	190	860	110	1/2"	Prever llave de corte en la toma
GAS	820	660	110	R.3/4"G	Prever regulador y llave de corte individual

